



FICHA TÉCNICA

PALETA PARE Y SIGA

ALTA INTENSIDAD 30 CM



DESCRIPCIÓN

Las Paletas Pare y Siga de 30 cm, están elaboradas en polietileno de alta densidad, con base cónica y reflectivo grado ingeniería.

USOS

Se utiliza para controlar el tráfico de vehículos y permitir el paso de peatones en zonas donde se están ejecutando obras públicas o simplemente en zonas donde hay algún evento masivo y hay exceso de personas y vehículos, se utiliza la paleta para no generar desorden.

CARACTERÍSTICAS

- ✓ COLOR PALETA: Blanca- Negra
- ✓ COLOR REFLECTIVO: Rojo- Verde
- ✓ Octogonal, paleta inyectada en una sola pieza
- ✓ MATERIAL: Polietileno de alta densidad - Reflectivo Alta Intensidad
- ✓ DIMENSIONES: Tablero octagonal de 30 cm x mango de agarre en pvc 12 cm -/+ 1 cm.

MATERIAL REFLECTIVO: Se utiliza reflectivos de Alta Intensidad Prismático Tipo IV - micropismático durable y de gran calidad que posee un adhesivo sensible a la presión. Su construcción micropismática única ofrece un alto nivel de retrorre reflectividad, su texto o logotipo es impreso con tintas translucidas resistentes a los rayos UV.



CARACTERÍSTICAS

-  COLOR BLANCO-NEGRO
-  MATERIAL POLIETILENO ALTA INTENSIDAD
-  REFLECTIVO ALTA INTENSIDAD
-  TABLERO OCTAGONAL DE 30 CM X MANGO DE AGARRE EN PVC 12 CM -/+ 1 CM.
-  550GR APROX

www.plastempack.com

SEDE PRINCIPAL

-  PBX: (57 - 601) 829 5743 - 829 5798
-  320 214 9004 - 321 983 4472
-  mercadeo@plastempack.com
-  Parque Industrial San Jorge Mz. P5 Bodega # 52 Troncal de Occidente Km 19 Vía Bogotá Mosquera Madrid - Colombia.

SEDE BOGOTÁ

-  PBX: (57 - 601) 261 3005 - 447 6304
-  320 344 8406 - 311 453 1985
-  comercial@plastempack.com
-  Carrera 65 # 4D - 34 Zona Industrial Pradera Bogotá D.C - Colombia



storex	Grade	SD-0150
	Resin Type	ABS

ABS material that can be used for typewriter and electric parts

Item	Measuring Method	Condition	Unit	Value
Physical				
Specific Gravity	ASTM D792	Natural Color	-	1.04
Melt Flow Index	ASTM D1238	200°C, 5kg	g/10min	2
Mechanical				
Tensile Strength	ASTM D638	5mm/min	MPa	41
Flexural Strength	ASTM D790	2.8mm/min	MPa	62
Flexural Modulus	ASTM D790	2.8mm/min	MPa	2000
IZOD Impact Strength (notched)	ASTM D256	1/4 inch	J/m	220
Rockwell Hardness	ASTM D785	R-Scale	-	109
Thermal				
VICAT Softening Temperature	ISO R 306	5kg	°C	99
Flammability				
Flammability	UL94	HB	mm	1.0, 1.5, 3.0, 6.0

1. The value above is the representative value of the NP standard and may have deviation. It can only be used for selecting materials.
2. The value above shall not be regarded as a material specification and cannot be used for molding designs.

Information inserted in this document such as data, statements, representative values, etc. are provided solely for customer convenience. It does not expressly or impliedly guarantee anything regarding the safety or practicability of the (1) materials, (2) products, and/or (3) design that utilizes recommendations or proposals, of Cheil Industries. Furthermore, nothing in the contents of this document shall have any legal binding effect, and especially, the representative value is simply for reference and is not a minimum value that has legal binding effect. Whether materials and/or products of Cheil Industries and/or a design that uses or utilizes Cheil Industries' recommendations or proposals are (is) compatible with individual uses shall be determined solely by each user and such user shall be solely responsible for any results, including but not limited to, any and all loss and damages incurred due to such uses. Users must implement and verify all testing and analyses for proving the safety and compatibility of final products that have been created or altered by using Cheil Industries' materials or products. The data and values inserted and/or contained in this document may be changed due to quality improvement of the product without any prior notification.

SEDE PRINCIPAL

- PBX: (57-601) 829 5743 - 829 5798
- 320 214 9004 - 321 983 4472
- mercadeo@plastempack.com
- Parque Industrial San Jorge Mz. P5 Bodega # 52 Troncal de Occidente Km 19 Vía Bogotá Mosquera Madrid - Colombia.

SEDE BOGOTÁ

- PBX: (57-601) 261 3005 - 447 6304
- 320 344 8406 - 311 453 1985
- comercial@plastempack.com
- Carrera 65 # 4D - 34 Zona Industrial Pradera Bogotá D.C - Colombia